

AMENDMENTS TO THE CLAIMS

1-47. (CANCELED).

48. (CURRENTLY AMENDED) A blood glucose monitoring system for monitoring a blood glucose level and for providing health-related information comprising:

(a) a display device including a display screen which displays the blood glucose level as measured;

(b) an audio speaker;

(c) a processor configured to provide audio and visual signals to the audio speaker and the display device respectively;

(d) at least one built-in memory including read-only digital memory (ROM) or writeable digital memory (RAM), or both, having stored therein operation data and operation software routines for:

(i) controlling the blood glucose monitoring system;

(ii) comparing the blood glucose level as measured with stored measurements;

(iii) performing one or more further processing functions in response to the comparing;

(iv) connecting to a remotely located computer in response to receiving an address of the remotely located computer from a removable memory card; and

(v) receiving the health-related information from the remotely located computer;

(e) at least one physiological data monitor configured to (i) provide a measurement signal representative of a physiological parameter of a user and (ii) ~~operate while being physically separated from said processor and~~ reside outside a first housing containing said processor;

(f) an interface device coupled between the processor
30 and the physiological data monitor to at least isolate electrically
the physiological data monitor from the processor while coupled
therebetween, wherein the electrically isolating interface device
is neither entirely disposed within said first housing containing
said processor nor any housing containing said physiological data
35 monitor; ~~and~~

(g) an input device in communication with the processor
and configured to: (i) receive an input from the user; (ii) enable
the user to (1) make selections and (2) control one or more user
functions of the blood glucose monitoring system; and (iii) provide
40 a control signal to the processor based upon the input, thereby to
cause the health related information to be provided to the user
based upon the measurement signal representative of the blood
glucose level and the control signal, wherein the physiological
parameter includes the blood glucose level and the physiological
45 data monitor includes a blood glucose indicator; and

(h) a cable coupling the interface device to the
processor.

49. (CANCELED).

50. (PREVIOUSLY PRESENTED) The system according to claim
48, wherein the interface device includes:

(a) a signal receiver for receiving the measurement
signal representative of the blood glucose level from the at least
5 one physiological data monitor;

(b) a converter for converting the measurement signal as
received into a form acceptable to the processor; and

(c) a processor controller for controlling the
processor.

51. (CURRENTLY AMENDED) A system for interactively monitoring a blood glucose level and for interactively providing health-related information comprising:

5 (a) a glucose monitor adapted to measure the blood glucose level of a user and for generating a first signal in response to a measurement of the blood glucose level;

10 (b) a processor (i) for receiving a second signal that is a function of the first signal, and (ii) being contained within a housing, ~~and (iii) configured to operate while being physically separated from said glucose monitor,~~ said glucose monitor being disposed outside said housing containing said processor;

15 (c) an interface device coupled between the blood glucose monitor and the processor: (i) for receiving the first signal from the blood glucose monitor; (ii) for providing the second signal to the processor; and (iii) configured to isolate electrically the user from the processor while coupled therebetween, wherein the electrically isolating interface device is neither entirely disposed within said housing containing said processor nor any housing containing said glucose monitor;

20 (d) a memory coupled to the processor for storing blood level data, the memory including read-only digital memory (ROM) or writeable digital memory (RAM), or both, having stored therein operation data and operation software routines for:

25 (i) controlling the system;
(ii) comparing the blood glucose level as measured with stored measurements;

(iii) performing one or more further processing functions in response to the comparing;

30 (iv) connecting to a remotely located computer in response to receiving an address of the remotely located computer from a removable memory card; and

(v) receiving the health-related information from the remotely located computer;

35 (e) a display system coupled to the processor for displaying a representation of the blood glucose level, so as to provide the health related information to the user in an interactive manner; ~~and~~

40 (f) an input device (i) in communication with the processor, (ii) enabling the user (1) to make selections and (2) to control one or more user functions of the system and (iii) provide a control signal to the processor based upon the input; and

(g) a cable coupling the interface device to the processor.

52. (PREVIOUSLY PRESENTED) The system according to claim 51, wherein the interface device utilizes optical isolation.

53. (CANCELED).

54. (CANCELED).

55. (PREVIOUSLY PRESENTED) The system according to claim 48 wherein the input device is hand-held.

56. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the input device receives the input from the user through at least one push button switch.

57. (CURRENTLY AMENDED) The system according to claim 48, wherein the health related information provided from the remotely located computer to the user includes moving images displayed on the display screen.

58. (CURRENTLY AMENDED) The system according to claim 57, wherein the health related information provided from the remotely located computer to the user further includes a comparison of measurements of the blood glucose level with previously stored measurements of the blood glucose level.

59. (CURRENTLY AMENDED) The system according to claim 57, wherein the health related information provided from the remotely located computer to the user includes educational information.

60. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the blood glucose monitoring system is configured to store particular information on the at least one built-in memory for later retrieval.

61. (CURRENTLY AMENDED) The system according to claim 48, wherein the display device is a television ~~display and the processor has at least one removable memory.~~

62. (CURRENTLY AMENDED) A method for monitoring a physiological condition and for providing health-related information with a system, the method comprising:

(a) using at least one physiological data monitor to provide a measurement signal representative of a user physiological parameter;

(b) providing a processor to produce audio and visual signals for reproduction at an audio speaker and a display screen, respectively, and (i) providing said processor within a housing, ~~and (ii) operating said processor while being physically separated from said physiological data monitor, and (iii) said physiological~~

data monitor being disposed outside said housing containing said processor;

15 (c) electrically isolating the processor and the physiological data monitor using an interface device while coupled between the processor and the physiological data monitor, wherein the electrical isolating occurs neither entirely within said housing containing said processor nor any housing containing said physiological data monitor;

20 (d) using an input device in communication with the processor to: (i) receive an input from the user; and (ii) provide one or more controller signals to the processor based upon the input from the user;

25 (e) in response to and based upon (i) the measurement signal representative of the user physiological parameter and (ii) the input from the user, having the processor cause the visual and the audio signals of the health related information to be presented to the user, wherein the user physiological parameter includes a blood glucose level and the physiological data monitor includes a blood glucose indicator; ~~and~~

30 (f) providing a memory coupled to the processor, the memory including read-only digital memory (ROM) or writeable digital memory (RAM), or both, the memory having stored therein the blood glucose level and operation software routines for:

35 (i) controlling the system;
(ii) comparing the blood glucose level as measured with stored measurements;

(iii) performing one or more further processing functions in response to the comparing;

40 (iv) connecting to a remotely located computer in response to receiving an address of the remotely located computer from a removable memory card; and

(v) receiving the health-related information from the remotely located computer; and

45 (g) coupling the interface device to the processor using a cable.

63. (CANCELED).

64. (PREVIOUSLY PRESENTED) The method according to claim 62, further comprising:

5 (a) receiving the measurement signal representative of the blood glucose level from the at least one physiological data monitor at the interface device;

 (b) converting the measurement signal as received into a form acceptable to the processor in the interface device; and

 (c) using a processor controller in the interface device for controlling the processor.

65. (PREVIOUSLY PRESENTED) The method according to claim 62, wherein the electrical isolation is achieved by optical isolation.

66. (CANCELED).

67. (CANCELED).

68. (PREVIOUSLY PRESENTED) The method according to claim 62 wherein the input device is hand-held.

69. (PREVIOUSLY PRESENTED) The method according to claim 62, wherein the input device receives the input from the user through at least one push button switch.

70. (CURRENTLY AMENDED) The method according to claim 62, wherein the health related information provided from the remotely located computer to the user includes moving images displayed on the display screen.

71. (CURRENTLY AMENDED) The method according to claim 70, wherein the health related information provided from the remotely located computer to the user further includes a comparison of measurements of the user physiological parameter with previously stored measurements of the user physiological parameter.

72. (CURRENTLY AMENDED) The method according to claim 70, wherein the health related information provided from the remotely located computer to the user includes educational information.

73. (PREVIOUSLY PRESENTED) The method according to claim 62, further comprising storing particular information in the memory for later retrieval.

74. (CURRENTLY AMENDED) The method according to claim 62, wherein the display screen comprises a television, and the visual signals are reproduced on the television ~~and the processor has at least one removable memory.~~

75. (CURRENTLY AMENDED) An apparatus for interactively monitoring a blood glucose level and for interactively providing health-related information comprising:

- a. a display device comprising a display screen;
- b. a processor coupled to provide a visual signal to the display screen, wherein the processor is contained within a housing;

c. an electrically isolating interface device coupled to the processor through a cable;

10 d. a glucose monitor coupled to provide a measurement signal representative of the blood glucose level to the electrically isolating interface device, wherein the glucose monitor is ~~(i) configured to operate while being physically separated from said processor and (ii)~~ outside said housing
15 containing said processor, wherein the electrically isolating interface device electrically isolates the processor from the glucose monitor while transferring the measurement signal and is neither entirely disposed within said housing containing said processor nor any housing containing said glucose monitor;

20 e. at least one built-in memory, including read-only digital memory (ROM) or writeable digital memory (RAM), or both, having stored therein operation data and operation software routines for:

(i) controlling the apparatus;
25 (ii) comparing the blood glucose level as measured with stored measurements;

(iii) performing one or more further processing functions in response to the comparing;

(iv) connecting to a remotely located computer in
30 response to receiving an address of the remotely located computer from a removable memory card; and

(v) receiving the health-related information from the remotely located computer; and

35 f. an input device in communication with the processor and configured to: (i) receive an input from the user; (ii) enable the user (1) to make selections and (2) to control one or more user functions of the apparatus; and (iii) provide a control signal to the processor based upon the input from the user.

76. (PREVIOUSLY PRESENTED) The apparatus according to claim 75 wherein the processor comprises a video game console.

77. (PREVIOUSLY PRESENTED) The apparatus according to claim 75 wherein the display device comprises a television set.

78. (PREVIOUSLY PRESENTED) The apparatus according to claim 75, further comprising:

a CD-ROM drive; and

5 an interchangeable compact disk removably coupled to the CD-ROM drive for providing additional functionality to the processor.

79. (PREVIOUSLY PRESENTED) The apparatus according to claim 75 wherein the electrically isolating interface device comprises:

5 a. means for receiving the measurement signal representative of the blood glucose level;

b. means for converting the measurement signal representative of the blood glucose level into a form acceptable to the processor coupled to the means for receiving; and

10 c. means for controlling the processor coupled to the means for converting.

80. (CANCELED).

81. (CURRENTLY AMENDED) An apparatus for interactively monitoring a blood glucose level and for interactively providing health-related information comprising:

5 a. a display device comprising a display screen and an audio speaker;

b. a processor contained within a housing and coupled to provide a visual signal to the display screen;

c. an electrically isolating interface device coupled to the processor through a cable;

5 d. a glucose monitor coupled to provide a measurement signal representative of the blood glucose level of a user to the electrically isolating interface device, wherein the glucose monitor is ~~(i) configured to operate while being physically separated from said processor and (ii)~~ outside said housing
10 containing said processor, wherein the electrically isolating interface device electrically isolates the processor from the glucose monitor while transferring the measurement signal and is neither entirely disposed within said housing containing said processor nor any housing containing said glucose monitor;

15 e. at least one built-in memory, including read-only digital memory (ROM) or writeable digital memory (RAM), or both, having stored therein operation data and operation software routines for:

(i) controlling the apparatus;

20 (ii) comparing the blood glucose level as measured with stored measurements;

(iii) performing one or more further processing functions in response to the comparing;

25 (iv) connecting to a remotely located computer in response to receiving an address of the remotely located computer from a removable memory card; and

(v) receiving the health-related information from the remotely located computer; and

30 f. an input device in communication with the processor and configured to: (i) receive an input from the user; (ii) enable the user to (1) make selections and (2) control one or more user

functions of the apparatus; and (iii) provide a control signal to the processor based upon the input.

82. (PREVIOUSLY PRESENTED) The apparatus according to claim 81 wherein the processor comprises a video game console.

83. (PREVIOUSLY PRESENTED) The apparatus according to claim 81 further comprising:

a CD-ROM drive; and

5 an interchangeable compact disk removably coupled to the CD-ROM drive for providing additional functionality to the processor.

84. (PREVIOUSLY PRESENTED) The apparatus according to claim 81 wherein the electrically isolating interface device comprises:

5 a. means for receiving the measurement signal representative of the blood glucose level;

b. means for converting the measurement signal representative of the blood glucose level into a form acceptable to the processor coupled to the means for receiving; and

10 c. means for controlling the processor coupled to the means for converting.

85-95. (CANCELED).

96. (PREVIOUSLY PRESENTED) The system according to claim 48, further comprising one or more communication ports configured to connect the blood glucose monitoring system to an "information superhighway".

97. (PREVIOUSLY PRESENTED) The system according to claim 48, further comprising a slot for accepting a flash memory card.

98. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the blood glucose monitoring system is configured for downloading particular information obtained from the user to a separate computer.

99. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the at least one built-in memory further has stored therein alarm data and alarm software routines for triggering an alarm if the blood glucose level as measured falls outside a predetermined range.

100. (PREVIOUSLY PRESENTED) The system according to claim 51, further comprising one or more communication ports configured to connect the system to an "information superhighway".

101. (PREVIOUSLY PRESENTED) The system according to claim 51, further comprising a slot for accepting a flash memory card.

102. (PREVIOUSLY PRESENTED) The system according to claim 51, wherein the system is configured for downloading particular information obtained from the user to a separate computer.

103. (PREVIOUSLY PRESENTED) The system according to claim 51, wherein the memory further has stored therein alarm data and alarm software routines for triggering an alarm if the blood glucose level as measured falls outside a predetermined range.

104. (PREVIOUSLY PRESENTED) The method according to claim 62, further comprising connecting to an "information superhighway".

105. (PREVIOUSLY PRESENTED) The method according to claim 62, further comprising accepting a flash memory card into a pre-configuration slot.

106. (PREVIOUSLY PRESENTED) The method according to claim 62, further comprising downloading particular information obtained from the user to a separate server.

107. (PREVIOUSLY PRESENTED) The method according to claim 62, wherein the memory further has stored therein alarm data and alarm software routines for triggering an alarm if the blood glucose level as measured falls outside a predetermined range.

108. (PREVIOUSLY PRESENTED) The apparatus according to claim 75, further comprising one or more communication ports configured to connect the system to an "information superhighway".

109. (PREVIOUSLY PRESENTED) The apparatus according to claim 75, further comprising a slot for accepting a flash memory card.

110. (PREVIOUSLY PRESENTED) The apparatus according to claim 75, wherein the apparatus is configured for downloading particular information obtained from the user to a separate computer.

111. (PREVIOUSLY PRESENTED) The apparatus according to claim 75, wherein the memory further has stored therein alarm data and alarm software routines for triggering an alarm if the blood glucose level as measured falls outside a predetermined range.

112. (PREVIOUSLY PRESENTED) The apparatus according to claim 81, further comprising one or more communication ports configured to connect the system to an "information superhighway".

113. (PREVIOUSLY PRESENTED) The apparatus of claim 81, further comprising a slot for accepting a flash memory card.

114. (PREVIOUSLY PRESENTED) The apparatus according to claim 81, wherein the apparatus is configured for downloading particular information obtained from the user to a separate computer.

115. (PREVIOUSLY PRESENTED) The apparatus according to claim 81, wherein the memory further has stored therein alarm data and alarm software routines for triggering an alarm if the blood glucose level as measured falls outside a predetermined range.

116. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the operational data and the operation software routines are configured to guide the user through additional measurements based on the comparing.

117. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the operational data and the operation software routines are configured to store particular information to support later retrieval or downloading based on the comparing.

118. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the operational data and the operation software routines are configured to recommend a certain action be taken by the user based on the comparing.

119. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the operational data and the operation software routines are configured to ask questions of the user based on the comparing.

120. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the operational data and the operation software routines are configured to give advice as to diet or exercise habits of the user based on the comparing.

121. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the input device is in wireless communications with the processor.

122. (PREVIOUSLY PRESENTED) The system according to claim 48, wherein the physiological data monitor and the input device are in a second housing separate from the first housing containing the processor.